



We protect
what matters most™

Premium Fabric

PRODUCT DESCRIPTION

GAF Premium Fabric is a tough, non-woven, stitch bonded polyester fabric that is designed for use as a reinforcing material in GAF coatings or Barrier-Guard® systems.

PACKAGING SIZES

300 ft long rolls, with the following widths: 4", 6", 8", 12", 16", 20", 24".

336 ft long rolls, with the following widths: 40".

WARRANTY

Refer to applicable warranties and guarantees, available at bmigroup.com/my, for complete coverage and restrictions.

APPLICATION INSTRUCTIONS

See instructions for the specific fabric-reinforced system being installed in the Liquid-Applied Roofing Manual at bmigroup.com/my

PHYSICAL PROPERTIES¹

Weight	3.0 ounces/yd ² 72 grams/m ²
Tensile Strength	MD: 70 lbs (56 kg) CD: 70 lbs (35 kg) [ASTM D5034]
Elongation	MD: 25% CD: 104% [ASTM D5034]
Ball Burst	114 lbs (49 kg) [ASTM D3787]
Trapezoidal Tear	MD: 27 lbs (7.7 kg) CD: 19 lbs (9.1 kg) [ASTM D3787]
Thickness	18 mils [ASTM D1777]

1. Values are approximate and subject to normal manufacturing variations. These values are not guaranteed and are provided solely as a guide.

SAFETY & HANDLING

For specific information regarding safe handling of this material, please refer to the Safety Data Sheet (SDS).

STORAGE

PRODUCT STORAGE TEMPERATURE: 50°F – 90°F (10°C – 32°C)

Keep BMI Premium Fabric in a clean, dry location.

APPROVALS

State of Florida Approved	FL620 and FL20663
Miami-Dade Approved	NOA 20-0105.10

BMI ROOFING SYSTEMS SDN. BHD.

Registration No. 197401002179 (19163-M)
(Formerly known as Monier Malaysia Sdn. Bhd.)
Suite 11.02, 11th Floor, Menara JKG,
No. 282, Jalan Raja Laut, 50350 Kuala Lumpur, Malaysia
T (+60) (3) 21760600 Toll Free: 1800 88 0865
roofing-malaysia@bmigroup.com

bmigroup.com/my